

BF80P



SUCTION CUP WITH SHORT BELLOWS

- ▶ Suitable for uneven surfaces.
- ▶ In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane.
- ▶ The material of the DURAFLEX® is mark free.

LIFTING FORCES & TECHNICAL DATA

Material	Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
PU30°/50°	73	157	196	54	88	117	40	132	15	53
PU60°	98	225	294	68	127	166	40	132	15	53

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU30	Yellow	30	10-50
Polyurethane, PU50	Blue transparent	50	10-50
Polyurethane, PU60	Green transparent	60	10-50

MATERIAL RESISTANCE

Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor

**Please contact Piab.

ORDERING INFORMATION

	Complete suction cups	Art. No.
A	Suction cup BF80P Polyurethane 30/50, G3/8" female	0102370
A	Suction cup BF80P Polyurethane 30/50, 3/8" NPSF female	0102371
A	Suction cup BF80P Polyurethane 60, G3/8" female	0103307
A	Suction cup BF80P Polyurethane 60, 3/8" NPSF female	0103309
B	Suction cup BF80P Polyurethane 30/50, G3/8" male with mesh filter	0107326
B	Suction cup BF80P Polyurethane 60, G3/8" male with mesh filter	0107327
B	Suction cup BF80P Polyurethane 30/50, G3/8" male	0106985
B	Suction cup BF80P Polyurethane 60, G3/8" male	0107476

