

FC100P



FLAT, CONCAVE SUCTION CUP WITH CLEATS

- ▶ Suitable for slightly domed and flat and oily surfaces, e.g., such as those encountered when handling steel sheets in press processes.
- ▶ Thanks to the high friction of the rubber material, the suction cups can withstand high forces at rapid accelerations in horizontal directions, even on oily surfaces.
- ▶ The suction cups have cleats that prevent thin objects from being disfigured.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

LIFTING FORCES & TECHNICAL DATA

Material	Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
PU40°	137	284	377	176	318	420	80	110	10.2	64
PU60°	152	328	446	112	264	382	80	110	10.2	64

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU40	Red transparent	40	10–50
Polyurethane, PU60	Green transparent	60	10–50


MATERIAL RESISTANCE

Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor


**Please contact Piab.

ORDERING INFORMATION

Complete suction cups		Art. No.
A	Suction cup FC100P Polyurethane 40, 1/8" NPSF female, with mesh filter	0103731
A	Suction cup FC100P Polyurethane 40, G3/8" female, with mesh filter	0103734
A	Suction cup FC100P Polyurethane 40, 3/8" NPSF female, with mesh filter	0103737
A	Suction cup FC100P Polyurethane 40, G1/2" female, with mesh filter	0103740
A	Suction cup FC100P Polyurethane 60, 1/8" NPSF female, with mesh filter	0103733
A	Suction cup FC100P Polyurethane 60, G3/8" female, with mesh filter	0103736
A	Suction cup FC100P Polyurethane 60, G1/2" female, with mesh filter	0103742
A	Suction cup FC100P Polyurethane 60, 3/8" NPSF female, with mesh filter	0103739
B	Suction cup FC100P Polyurethane 40, thread insert G3/8" male, with mesh filter	0106836
B	Suction cup FC100P Polyurethane 60, thread insert G3/8" male, with mesh filter	0107305
C	Suction cup FC100P Polyurethane 40, 3/8" NPSF female	0108798
C	Suction cup FC100P Polyurethane 60, 3/8" NPSF female	0108799



Rubber parts		Art. No.
A	Suction cup FC100P Polyurethane 40	0103297
A	Suction cup FC100P Polyurethane 60	0103299
B	Suction cup FC100P Polyurethane 40, for tread insert	0106835
B	Suction cup FC100P Polyurethane 60, for tread insert	0107304



Fittings		Art. No.
Fitting 75, 1/8" NPSF female, with mesh filter		0100548
Fitting 75, G3/8" female, with mesh filter		0100551
Fitting 75, 3/8" NPSF female, with mesh filter		0100553
Fitting 75, G1/2" female, with mesh filter		0100555
Thread insert G3/8" male, with O-ring and mesh filter		0107148

For further information and dimensioned drawings, see SUCTION CUPS FITTINGS chapter.