

FC20P



FLAT, CONCAVE SUCTION CUP WITH CLEATS

- ▶ Suitable for lifting small objects and narrow parts, also slightly domed, flat and oily surfaces, e.g., such as those encountered when handling steel sheets in press processes.
- ▶ Thanks to the high friction of the rubber material, the suction cups can withstand high forces at rapid accelerations in horizontal directions, even on oily surfaces.
- ▶ The suction cups have cleats that prevent thin objects from being disfigured.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
4.5	12.0	16.0	4.5	9.0	12.0	1.0	25	1.9	1.3

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU50	Blue transparent	50	10–50


MATERIAL RESISTANCE

Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor


**Please contact Piab.

ORDERING INFORMATION


Complete suction cups		Art. No.
A	Suction cup FC20P Polyurethane 50, M5 female	0106717
B	Suction cup FC20P Polyurethane 50, G1/8" male, with mesh filter	0106722
C	Suction cup FC20P Polyurethane 50, G1/8" male / M5 female, with mesh filter	0106718



A



B



C

Rubber part		Art. No.
Suction cup FC20P Polyurethane 50		0106016



Fittings		Art. No.
Fitting M5 female		3250003
Fitting G1/8" male, with mesh filter		3250085
Fitting G1/8" male/M5 female, with mesh filter		0101152

For further information and dimensioned drawings, see *SUCTION CUPS FITTINGS* chapter.

Suction cups
FC-P