

## U15-3



### UNIVERSAL SUCTION CUP WITH REINFORCED LIP

- ▶ Wide temperature range (-60°C to +200°C)
- ▶ The silicone material complies with FDA 21 CFR 177.2600
- ▶ Reinforced lip

### LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm <sup>3</sup>	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
3.5	8.4	11.0	3.5	5.4	5.9	0.50	8.0	1.5	0.70

### MATERIAL SPECIFICATIONS


Material	Colour	Hardness °Shore A	Temperature range °C
Silicone, SIL	Red	40	-40-200

### MATERIAL RESISTANCE


Material	Wear resistance	Oil	Weather & Ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

### ORDERING INFORMATION

Complete suction cup	Art. No.
Suction cup U15-3 Silicone, M5 male	0117947



Rubber part	Art. No.
Suction cup U15-3 Silicone	0114981



Fittings	Art. No.
Fitting M5 male, 10-15	3107030

For further information and dimensioned drawings, see *SUCTION CUPS FITTINGS* chapter.